

CABLE – MINI RG59 75 OHM, 95% BRAID

All cables have 23 AWG solid bare copper conductors, a 100% bonded foil shield and 95% tinned copper braid shield. The small O.D. enables a 1.5" bend radius – ideal where space is at a premium. These cables meet SMPTE Broadcast Digital Standards (SDI). Available in 100', 250' and 1000' spools.



Part Number	Description	Nominal O.D. (in)	Nominal Wt. (lb/1000')
YR46940	RG59 mini 75 Ohm video, bonded foil Available in brown, red, orange, yellow, blue, violet, gray, white, black, green and aqua.	0.159	17.0
YR47051	RG59 mini 75 Ohm video, bonded foil, dual white	Siamese	34.0
YR46941	RG59 mini 75 Ohm video, bonded foil, 3-pack black (RGB)	0.440	93.0
YR48335	RG59 mini 75 Ohm video, bonded foil, 4-pack	0.481	109.0
YR46942	RG59 mini 75 Ohm video, bonded foil, 5-pack black jacket (RD GN BL WH YL)	0.593	147.0
YR47075	RG59 mini 75 Ohm video, bonded foil, 5-pack (RD GN BL BK-R BK-L) Available in black and white	0.593	147.0
YR47193	RG59 mini 75 Ohm video, bonded foil, 8-pack Available in brown, red, orange, yellow, blue, violet, gray, white, black, and green	0.638	214.0
YR46943	RG59 mini 75 Ohm video, bonded foil, 10-pack black (rainbow conductors)	0.796	323.0
YR47172	RG59 mini 75 Ohm video, bonded foil, 10-pack Available in red, blue, white, and green	0.796	323.0
YR48336	RG59 mini 75 Ohm video, bonded foil, 12-pack Available in red and blue	0.825	353.0
YR48327	RG59 mini 75 Ohm video, bonded foil, 16-pack Available in red, blue, black and in black in brown singles	0.916	464.0
YR50390010	Mini RG59 Tri-Shield, Single, Black	0.164	20.0

CABLE – MINI RG59 75 OHM, PLENUM RATED

All cables have 23 AWG solid bar copper conductors, a 100" bonded foil shield and 95% tinned copper braid shield.

Part Number	Description	Nominal O.D. (in)	Nominal Wt. (lb/1000')
YR53024	RG59 mini 75 Ohm video, bonded foil, 95% braid, plenum Available in yellow, gray, black and white	0.159	22.0